

## Blind NS2545 PN10 Flange Dimensions

### BLIND NS2545 PN10 FLANGE DIMENSIONS

DN	flange				Bolts			weight
	Dia. D mm	t mm	d1 mm	k mm	no.	size	d2 mm	kg/ea
200	340	24	190	295	8	M 20	22	17
250	395	26	235	350	12	M 20	22	24.5
300	445	26	285	400	12	M 20	22	31.8
350	506	26	330	460	16	M20	22	41
400	565	26	380	515	16	M24	26	51.2
450	615	28	425	565	20	M24	26	65.2
500	670	28	475	620	20	M24	26	78
600	780	32	580	725	20	M27	30	121
700	895	36	680	840	24	M27	30	179
800	1015	40	785	950	24	M27	30	255
For ND15-175 see NS2546								

### BLIND NS2545 PN10 FLANGE DIMENSIONS INDUSTRIES AND APPLICATIONS WIDELY USED IN THE INDUSTRIES

- Pumps, Valves, and vessels in manufacturing and food processing.
- Pipe connections in industrial waterworks.
- Heat exchangers and heating systems of all sizes.
- Mining support.
- Nuclear power systems.
- Plumbing and mechanical systems.
- Assemblies in the oil, gas, and petrochemical industries.
- Fire protection systems.